

Series 1 FRLs

F73-Series Compact Airline Filters

Features

- Particle removal per ISO 8573-1, Class 5, and Class 3
- 40 micron element
- 4 oz. reservoir
- Quick-release bayonet bowl
- Prismatic lens liquid level indicator

Specifications

- Inlet pressure:
 - transparent bowl: max pressure **150 PSIG (10 bar)** and temperature range **-30°F (-34°C to 50°C)**
 - metal bowl: max pressure **250 PSIG (17 bar)** and temperature range **-30°F to 150°F (-34°C to 66°C)**



with transparent bowl




with metal bowl

Transparent Bowl


Port Size	Flow (SCFM)	Automatic Drain Part #	Manual Drain Part #
1/4"	53	F73G-2A	F73G-2M
3/8"	65	F73G-3A	F73G-3M
1/2"	69	F73G-4A	F73G-4M

Metal Bowl and Sight Glass

Port Size	Flow (SCFM)	Automatic Drain Part #	Manual Drain Part #
1/4"	53	F73G-2A-MB	F73G-2M-MB
3/8"	65	F73G-3A-MB	F73G-3M-MB
1/2"	69	F73G-4A-MB	F73G-4M-MB



** Minimum clearance required to remove bowl.



1/4 Turn Manual Drain
** Minimum clearance required to remove bowl.

F74-Series Standard Airline Filters

Features

- Particle removal per ISO 8573-1, Class 5, and Class 3
- 40 micron element
- 7 oz. reservoir
- Quick-release bayonet bowl
- Prismatic lens liquid level indicator

Specifications

- Inlet pressure:
 - transparent bowl: max pressure **150 PSIG (10 bar)** and temperature range **-30°F to 125°F (-34°C to 50°C)**
 - metal bowl: max pressure **250 PSIG (17 bar)** and temperature range **-30°F to 150°F (-34°C to 66°C)**



with transparent bowl




with metal bowl

Transparent Bowl and Guard


Port Size	Flow (SCFM)	Automatic Drain Part #	Manual Drain Part #
3/8"	112	F74G-3A	F74G-3M
1/2"	140	F74G-4A	F74G-4M
3/4"	140	F74G-6A	F74G-6M

Metal Bowl and Sight Glass

Port Size	Flow (SCFM)	Automatic Drain Part #	Manual Drain Part #
3/8"	112	F74G-3A-MB	F74G-3M-MB
1/2"	140	F74G-4A-MB	F74G-4M-MB
3/4"	140	F74G-6A-MB	F74G-6M-MB



** Minimum clearance required to remove bowl.



** Minimum clearance required to remove bowl.

NOTE: See pages 343-348 for accessories.

FRLs are designed for air service only, unless otherwise indicated.
SCFM ratings at 90 PSIG inlet pressure.

