

Worm Gear Clamps

Features

- Four-piece construction
- Screw design: 5/16" slotted hex head
- Maximum recommended torque: 50 in. lbs.
- All clamps sold 10 per box

Materials

- Band and housing: SAE 300 series stainless
- Screw: SAE 300 series stainless

Approval

- Clamp meets SAEJ1508, which supersedes Mil Spec WW-C-440B



| Band Width | Hose O.D. | | Kit Contains Part # | Required Case Qty | Part # |
|------------|-----------|---------|---------------------|-------------------|-----------|
| | From | To | | | |
| 1/2" | 1/2" | 29/32" | HSS8 | 40 | GHD-HSS8 |
| | 11/16" | 1-1/14" | HSS12 | 40 | GHD-HSS12 |

Rubber Vinyl Garden Hose

Features

- Extra tough, five-ply construction
- Exclusive, soft textured, abrasion-resistant green cover
- Dual reinforced, heavy-duty, flexible kink-resistance
- Combines durability of rubber and easy handling of vinyl
- SEAL-TITE leakproof coupling

Specifications

- Working pressure: 400 PSI
- Temperature range: 0°F to 140°F (-18°C to 60°C)



| Size | Required Case Qty | Rubber Vinyl Part # |
|------------|-------------------|---------------------|
| 5/8" x 50' | 2 | GHD-SGH50 |

Contractors EPDM Water Hose

Features

- Heavy-duty, crush-proof solid brass couplings with wrench grips
- Spiral synthetic cord reinforcement
- Black cover

Specifications

- Working pressure: 150 PSI
- Temperature range: -20°F to 180°F (-29°C to 82°C)



| Size | Required Case Qty | EPDM Part # |
|------------|-------------------|-------------|
| 3/4" x 50' | 2 | GHD-CWH50 |