Overfill Protection Rack Monitor

Rack Monitor System

FT7000
Rack Monitor

FT7500
Junction Box

FT600
Rack Cord

Rack Monitor

Application
- Installed on the gantry to control the loading process of petroleum fuels or other hazardous liquid into cargo tanks

Features
- Automatically switches between 2-wire or 5-wire type sensors
- Compatible with analog 2-wire thermistor type sensors
- Redundant relay outputs prevent single point failures
- Data management via RS485 port
- Wireless bypass key system
- Ground verification
- Reads trailer identification modules

Approvals
- Meets API RP1004 and EN13922 standards
- Suitable for Class I, Division 1, Group CD and Class I, Zone 1, and Group IIB
- Rated to IP66

Dixon Bayco®

7280 Union Centre Blvd
West Chester, Ohio 45014
ph: 513.874.8499
fx: 513.874.8399
dixonvalve.com

Order Guide

Part #	Rack Monitor Description
FT7000	rack monitor, auto switch between 2-wire / 5-wire sensors, ground verification, and trailer identification modules; API RP 1004 / EN13922

	Safe-T Connect Junction Box Description
FT7600	8-pin, 4J, green API plug, and 30' safety orange coiled cable
FT7600C	10-pin, 4J, green API plug, and 30' safety orange coiled cable
FT7600P	8-pin, 4J, green API plug, 30' safety orange coiled cable, and Plug-n-Play connector
FT7600S	8-pin, 4J, green API plug, and 20' safety orange straight cable
FT7620	6-pin, 3J, blue API plug, and 30' blue coiled cable
FT7620P	6-pin, 3J, blue API plug, 30' blue coiled cable, and Plug-n-Play connector
FT7620S	6-pin, 3J, blue API plug, and 20' blue straight cable
FT7630	10-pin, 4J, black plug per EN13922, and 30' blue shielded coiled cable
FT7630D	10-pin, 4J, black plug per EN13922, and 30' blue shielded coiled cable with Dixon Bayco break-away

	Junction Box Description
FT7500	single cord junction box
FT7501	dual cord junction box
FT7502	junction box with Cole Hersee yellow 13-pin break-away
FT7503	junction box with D-type pigtail break-away
FT7504	junction box w/ aluminum D-connector break-away

	Rack Cord Description
FT600	8-pin, 4J, API thermistor plug, and 30' safety orange coiled cable
FT600C	10-pin, 4J, API thermistor plug, and 30' safety orange coiled cable
FT600D	API thermistor plug w/ 30' coiled cable w/ aluminum D-connector break-away
FT600CD	API thermistor plug w/ 30' coiled cable w/ 13P CA 4J 10-pin aluminum D-connector break-away
FT600P	8-pin, 4J, API thermistor plug, and 30' safety orange coiled cable with 13-pin Plug-n-Play
FT600S	8-pin, 4J, API thermistor plug, and 20' safety orange straight cable
FT620D	API optic plug w/30' coiled cable w/ aluminum D-connector break-away
FT620	6-pin, 3J, API optic plug, and 30" blue coiled cable
FT620P	6-pin, 3J, API optic plug, 30' blue coiled cable and Plug-n-Play connector
FT620S	6-pin, 3J, API optic plug, and 20' blue straight cable
FT630	10-pin, 4J, black plug per EN13922, and 30' blue shielded coiled cable
FT630D	10-pin, 4J, black plug per EN13922, 30' blue shielded coiled cable, and Dixon Bayco break-away

Winnipeg, Canada
2200 Logan Ave
Winnipeg, MB R2R 0J2,
Canada
ph 800.963.4966
fx 877.436.6251

Wingfield SA, Australia
170 Francis Rd
Wingfield SA 5013
Australia
ph 61.8.8202.6000
fx 61.8.8202.6099

Monterrey, Mexico
Ave Churubusco 1600 L-14
Col Francisco | Madero
Monterrey N.I., MX 54560
ph 52.81.8354.5649
fx 52.81.8354.8197

Singapore
25B Loyang Crescent
Blk 302 #02-08
Singapore 506817
ph 65 6232 5272
fx 65 6232 5270

Shanghai, China
Room 1201 Sun Building
No 3553 North Zhongshan Rd
Putuo District
Shanghai 200063, China
ph 86 021 6173 7998
fx 86 021 6173 8589